FAX NO.

AMENDMENT

In the Claims:

Please amend the claims according to the following listing of claims and substitute it for all prior versions and listings of claims in the application.

Claim 1. (currently amended) An apparatus for measuring optoelectric properties of an organic light-emitting device (OLED), comprising:

a platform;

a goniometer disposed on one side of the platform, wherein an OLED is attached to the goniometer;

a three-axis moving device disposed on another side of the platform;

a photo-detector disposed on the three-axis moving device, wherein the photo-detector is oriented in a direction toward the OLED on the goniometer; and

a computer linked to the goniometer, the three-axis moving device and the photo-detector.

Claim 2. (currently amended) The apparatus of claim 1, wherein the goniometer is capable of rotating and/or tilting.

Claim 3. (original) The apparatus of claim 1, wherein the three-axis moving device has

mechanisms for moving forward and backward (in the X direction), up and down (in the Y

direction) and left and right (in the Z direction).

Claim 4. (currently amended) The apparatus of claim 1, wherein the computer controls

the movement of the three-axis moving device, the rotation and/or tilting of the goniometer and

the recording of measured data obtained from the photo-detector.

Claim 5. (original) The apparatus of claim 1, wherein the photo-detector further

comprises a brightness-measuring device for measuring the brightness level, coloration, viewing

angle and uniformity of the OLED.

Claim 6. (cancelled)

Claim 7. (original) The apparatus of claim 1, wherein the apparatus further comprises a

power supply controlled by the computer for driving the OLED.

Claim 8. (currently amended) The apparatus of claim 7, wherein the apparatus further

comprises a current driver connected to the power supply and controlled by the computer for

measuring the response time of an the OLED under predetermined conditions.

3

Claim 9. (currently amended) An apparatus for measuring optoelectric properties of an organic light-emitting device (OLED), comprising:

a platform;

a goniometer disposed on one side of the platform, wherein an OLED is attached to the goniometer;

a three-axis moving device disposed on another side of the platform;

a brightness detector disposed on the three-axis moving device, wherein the brightness detector is oriented in a direction toward the OLED on the goniometer; and

a computer linked to the goniometer, the three-axis moving device and the brightness detector.

Claim 10. (currently amended) The apparatus of claim 9, wherein the goniometer is capable of rotating and/or tilting.

Claim 11. (original) The apparatus of claim 9, wherein the three-axis moving device has mechanisms for moving forward and backward (in the X direction), up and down (in the Y direction) and left and right (in the Z direction).

NOV-14-2005 MON 16:21 FAX NO. P. 06/13

Customer No.: 31561 Docket No.: 9705-US-PA Application No.: 10/707,648

Claim 12. (currently amended) The apparatus of claim 9, wherein the computer controls

the movement of the three-axis moving device, the rotation and/or tilting of the goniometer and

the recording of measured data obtained from the brightness detector.

Claim 13. (cancelled)

Claim 14. (original) The apparatus of claim 9, wherein the apparatus further comprises a

power supply controlled by the computer for driving the OLED.

Claim 15. (currently amended) The apparatus of claim 14, wherein the apparatus further

comprises a current driver connected to the power supply and controlled by the computer for

measuring the response time of an the OLED under predetermined conditions.

Claim 16. (currently amended) A method of measuring the optoelectric properties of the

an organic light omitting device (OLED) using an the apparatus described in claim 1, comprising

the steps of:

programming the computer to drive the OLED via the power supply and to remotely

control the photo-detector;

programming the computer to drive the three-axis moving device to a specified location,

and rotate and/or tilt the OLED on the goniometer to a specified angle;

5

measuring the optoelectric properties of the OLED using the photo-detector; and recording the data measured by the photo-detector into the computer automatically.

Claim 17. (original) The method of claim 16, wherein the computer further carries out a data processing, graph plotting and statistical analysis on the data measured by the photo-detector.

Claim 18. (original) The method of claim 16, wherein the optoelectric properties of the OLED comprises the brightness, the coloration, the viewing angle, the uniformity, the contrast ratio and the response time of the OLED.